

GENERAC®

Commercial Power Washers

Power Washers



3100 psi - Model 006590-0 (49-State & Canada)
UPC: 696471065909

Model 006607-0 (50-State)
UPC: 696471066074

3800 psi - Model 006564-0 (49-State & Canada)
UPC: 696471065640

4200 psi - Model 006565-0 (49-State & Canada)
UPC: 696471065657



*Built in the USA using domestic
and foreign parts

FEATURES

PRO-GRADE TRIPLEX PUMP

- Up to 4X longer life than axial cam pumps

POWERFUL GENERAC OHV ENGINE

- Delivers maximum cleaning performance and reliability

STEEL-REINFORCED HOSE

- Durable, non-marring hose will not leave scuff marks

FOLDING HANDLE

- For compact storage and transport

WELDED ROLL CAGE FRAME

- Protects components and provides gripping surfaces for easier lifting

BRASS QUICK CHANGE FITTINGS

- For faster connections

PRESSURE CONTROL VALVE

- For adjustable cleaning power

PROFESSIONAL SPRAY GUN

- Quick change connections, stabilizing side handle, molded grip, and easier-to-pull trigger for comfort during prolonged use

3100 • 3800 • 4200 psi
specifications
PRESSURE AND FLOW

| | |
|-------------------------------|--|
| Max Outlet Pressure (psi/bar) | 3100/213 - 006590-0 & 006607-0 3800/262 - 006564-0 4200/290 - 006565-0 |
| Max Flow Rate (gpm)/(L/min) | 2.8/10.6 - 3100 psi 3.6/13.6 - 3800 psi 4.0/15.1 - 4200 psi |

ENGINE

| | |
|------------------------------------|---|
| Manufacturer | Generac |
| Displacement (in ³ /cc) | 12.9/212 - 3100 psi 18.4/302 - 3800 psi 25.6/420 - 4200 psi |
| Type | OHV (Overhead Valve) |
| Orientation | Horizontal |
| Low Oil Shutdown System | Yes |
| Fuel Capacity (gal/L) | 0.8/3 - 3100 psi 1.5/5.7 - 3800 psi 1.6/6.1 - 4200psi |
| Fuel On/Off Switch | Yes |
| Oil Capacity (oz/L) | 20/0.6 - 3100 psi 37/1.1 - 3800 & 4200 psi |
| Recommended Engine Oil | SAE 30 or 10W30 |
| Throttle Control | Manual |
| Choke | Manual |
| Starting Method | Manual/Recoil |

PUMP

| | |
|--|--------------------------------|
| Type | Triplex |
| Plunger | Ceramic-coated stainless steel |
| Maximum Water Supply Temperature (°F/°C) | 100/38 |

HOSE

| | |
|------------------|---|
| Length (ft/m) | 35/10.7 - 3100 & 3800 psi 50/15.2 - 4200 psi |
| Rating (psi/bar) | 4000/276 - 3100 & 3800 psi 4200/290 - 4200 psi |
| Connectors | Quick change |

NOZZLES

| | |
|----------------------------|---------------------|
| Number of Nozzles per Unit | 5 |
| Nozzle Descriptions | 0, 15, 25, 40, soap |

GUN & LANCE

| | |
|----------------------------|---|
| Gun Type | Professional |
| Gun to Lance Connection | Quick Change |
| Gun to Hose Connection | Quick Change |
| Lance Length (in/cm) | 20/51 - 3100 psi 33/84 - 3800 & 4200 psi |
| Lance to Nozzle Connection | Quick change |

FRAME & MISC.

| | |
|--------------------|---|
| Handle | Folding |
| Frame Construction | Welded steel |
| Wheels (in/cm) | 3 x 10/7.6 x 25.4 Never flat - 3100 & 3800 psi 4 x 12/10.2 x 30.5 pneumatic - 4200 psi |

DIMENSIONS & WEIGHTS

| | |
|-------------------------------|---|
| Length (in/cm) | 31.8/80.6 - 3100 psi 34.5/87.6 - 3800 & 4200 psi |
| Width (wheel to wheel, in/cm) | 24.3/61.6 - 3100 psi 26.8/67.9 - 3800 psi 28.3/71.8 - 4200 psi |
| Height (in/cm) | 38/96.5 - 3100 psi 42.5/108 - 3800 & 4200 psi |
| Unit Weight (lbs/kg) | 102.5/46.5 - 3100 psi 129/58.5 - 3800 psi 146.5/66.5 - 4200 psi |
| Boxed Length (in/cm) | 26/66 - 3100 psi 29/73.7 - 3800 & 4200 psi |
| Boxed Width (in/cm) | 25.5/64.8 - 3100 psi 28/71.1 - 3800 & 4200 psi |
| Boxed Height (in/cm) | 31/78.7 - 3100 psi 33.5/85.1 - 3800 & 4200 psi |
| Boxed Weight (lbs/kg) | 120/54.4 - 3100 psi 150/68 - 3800 psi 164/74.4 - 4200 psi |

WARRANTY

| | |
|----------|----------------|
| Warranty | 3 year limited |
|----------|----------------|